



IC-V3MR

MULTI-USE RADIO SERVICE (MURS) TRANSCEIVER

License Free

IP54 and MIL-STD 810G
Tough and Rugged Body



2 Watts Output and All 5 MURS
Frequencies for Business Use


High Capacity Li-ion Battery
24 hours Operational Time
(5/5/90 duty)

Made in Japan Quality
Full Robotic Assembly

1500 mW (typ.) Powerful
Audio with BTL Amplifier



Optional 1500mW
Speaker-Microphone,
HM-222HLWP



Rugged, Loud and Reliable



2 Year
Warranty

Other Features

- VOX (Voice Operated Transmit) function
- MDC PTT ID transmit
- CTCSS Tone and DTCS code
- DTMF functions
- Emergency and Lone Worker functions
- 2-step low battery beep
- Customizable settings with PC programming software (free download)
- FCC Certified

Communication Range

Up to **250,000** sq ft in a building*  Up to **20** floors in a building*  Up to **2** miles in a work site* 

*Communication range may differ depending on operating environment or weather conditions, etc.

SPECIFICATIONS

Usable frequencies (bandwidth)	151.820 MHz (11.25 kHz), 151.880 MHz (11.25 kHz), 151.940 MHz (11.25 kHz), 154.570 MHz (20.00 kHz), 154.600 MHz (20.00 kHz)
No. of memory channels	16 ch
Transmit output power	2 W (High), 1 W (Mid), 0.5 W (Low)
Receiver sensitivity	0.25 µV (typical) for 12 dB SINAD
Squelch sensitivity	0.25 µV (typical) at squelch threshold point
Audio output power (at 5% distortion, 8 Ω load)	Internal SP 1.5 W (typical) External SP 0.4 W (typical) HM-222HLWP 1.5 W (typical)
Antenna impedance	50 Ω
Power supply voltage	7.2 V DC
Current drain	Receive stand-by 75 mA Receive max. audio 500 mA Transmit (High) 0.9 A
Dimensions (Projections not included)	58 (W) × 111 (H) × 35.5 (D) mm, 2.3 (W) × 4.4 (H) × 1.4 (D) in (with BP-298)
Weight (Approximate)	265 g, 9.3 oz (with BP-298)

All stated specifications are subject to change without notice or obligation. Measurements made in accordance with TIA-603.

Applicable U.S. Military Specifications

Standard	MIL 810G	
	Method	Procedure
Low Pressure	500.5	I, II
High Temperature	501.5	I, II
Low Temperature	502.5	I, II
Temperature Shock	503.5	I-C
Solar Radiation	505.5	I
Rain Blowing/Drip	506.5	I, III
Humidity	507.5	II
Salt Fog	509.5	-
Dust Blowing	510.5	I
Vibration	514.6	I
Shock	516.6	I, IV

Also meets equivalent MIL-STD-810-C, -D, -E and -F.

Ingress Protection Standard	
Dust & Water	IP54 (Dust-protection and splash resistant)

Supplied Accessories:

- BP-298 Battery Pack • BC-240 Rapid Charger • BC-242 AC Adapter
- MB-124 Belt Clip • FA-SC28V Antenna

OPTIONAL ACCESSORIES

SPEAKER MICROPHONES



HM-222HLWP
High-power audio speaker with 3.5 mm earphone jack



HM-158LA
Compact speaker microphone with 3.5 mm earphone jack



HM-159LA
Loud and clear audio speaker microphone

HEADSETS



HS-94 Earhook type headset
HS-95 Neck-arm type headset
HS-97 Headset with throat microphone

PTT SWITCH CABLES



OPC-2004LA Plug adapter cable for VOX operation
VS-4LA PTT switch cable for manual PTT operation

(Either the VS-4LA or OPC-2004LA is required for use with the HS-94, HS-95 or HS-97.)

BATTERY PACK

BP-298 Li-ion, 2250 mAh (typ.), 2100 mAh (min.) (Same as supplied.)



OTHER ACCESSORIES

MB-124 Belt clips (Same as supplied)

FA-SC28V Antennas 148-162 MHz (Same as supplied)

RAPID CHARGER



BC-242 **BC-240**

Charges the BP-298 in 3 hours (approx.). The BC-242 is supplied with the BC-240.

MULTI-CHARGER



BC-157S **BC-214N**

The BC-157S and AD-139 charger adapters are supplied with the BC-214N, depending on the charger version.

CIGARETTE LIGHTER CABLE & POWER SUPPLY CABLES



CP-23L
For use with BC-240



OPC-515L
For use with BC-240



OPC-656
For use with BC-214N

PROGRAMMING SOFTWARE & CABLE

CS-V3MR
Programming software for Windows™ PC
Available for free download from:
https://www.icomjapan.com/support/firmware_driver/

OPC-478UC
Programming cable (USB)

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. Windows is a trademark of the Microsoft group of companies. All other trademarks are the properties of their respective holders.

Your local distributor/dealer: