VP-GK-5UT



Universal Grounding Kit for Cable and Assemblies
one size fits all design, 5 foot, 6 AWG lead with unattached two-hole lug

Includes grounding kit, lug, butyl tape, electrical tape

General

Cable Type	hybrid, power, corrugated, smoothwall
Grounding Kit Type	universal
Universal Ground Strap	tinned copper
Lead Conductor Material	6 AWG, insulated copper wire
Waterproof Method	butyl and electrical tape
Grounding Lug Type	2 hole lug, tinned copper
Lug Attachment Hardwares	stainless steel

Environmental / Mechanical

Operating Temperature	-40°C to +80°C (-40°F to +176°F)
Storage Temperature	-30°C to +80°C (-22°F to +176°F)
Installation Temperature	-20°C to +80°C (-4°F to +176°F)
Compliance	MIL-STD-188-124A to withstand an excess of 200kA
Ordering Note	recommended at the top and bottom of each vertical run at 200 ft increments and just prior to building entry

Dimensions

Lead Conductor Length	1524.0 mm (5 ft)
Cable Diameter Range	15.5 - 50.8 mm (0.61 - 2.0 in)
Cable Jacketing Removal Length	56 - 59 mm (2.2 -2.3 in)
Thread Size	9.525 mm (0.375 in)
Weight	0.71 kg (1.56 lb)

©2022 viaPhoton, Inc. All rights reserved.