SPECIFICATION

4K x 2K HDMI Extender, Cat 5E/6 for 120 meters
for use in Kit TT683-4.0

Model	TT683-4.0 RX
Technique	
HDMI Compliance	HDMI 1.4
HDCP Compliance	HDCP1.3
Transport Protocol	HDbitT
Transmission medium	Network cable
Transmission distance	CAT5: 80m, CAT5e: 100m, CAT6: 120m
Video bandwidth	18Mbps(10.2G)
Supported resolutions	480i@60Hz,480p@60Hz,576i@50Hz,576p@50Hz,720p@50/60Hz, 1080i@50/60Hz,1080p@50/60Hz,4Kx2K@24/25/30Hz
Audio support	PCM
TMDS input signal	0.7~1.2Vp-p
DDC input signal	5Vp-p
HDMI Loop Out	No
RS232 support	No
POE Support	No
Multiple Receiver Connection	Yeah
Return IR	Yeah
IR frequency range	20-60Khz
Entrance	DC2.1, RJ45 ×1, 3.5mm Audio F ×1 (IR)
Exit	1×HDMI
HDMI Source Control	Controllable via IR Passback from RX to TX
HDMI connector	Type A, female, 19 pins
Mechanic	
Accommodation	Metal enclosure
Dimensions	107.3mm(L) x 94mm(W) x 23.7mm(H)
Net weight	RX: 167g
Power supply	5V/2A
Consumption	4W
Operating temperature	0~60ÿ
Storage temperature	-20ÿ70ÿ
Relative humidity	0ÿ95%(non-condensing)